

HUNTER PENROSE

printing materials and equipment

Hunter Penrose Supplies Ltd
32 Southwark St, London, SE1 1TU
0207 407 5051 fax 0207 378 1800

e-mail: info@hunterpenrosesupplies.co.uk

equipment data sheet

light tables

model ref: FAG ruling-up tables

Description

Ruling-up light table with horizontal and vertical rules, adjustable height and angle.

Extremely well engineered precision construction.

- precision matched chain drives for cursors.
- precision manufactured straight edges
- cursors bevel edged
- satin chromed cursors
- built-in film grips on lay blocks.
- lay blocks lockable.
- colour corrected light tubes
- heavy perspex diffuser
- rigid steel construction



Specification

Model	No. 1	No. 2	No. 3	No. 4
Paper size	A2 plus	A1 plus	A0	A0 plus
Illuminated area	585 x 789mm (23" x 31")	699 x 1004mm (27 1/2" x 39 1/2")	902 x 1169mm (35 1/2" x 46")	1118 x 1398mm (44" x 55")
Glass & perspex size	607 x 810mm (23 7/8" x 31 7/8")	721 x 1026mm (28 3/8" x 40 3/8")	924 x 1191mm (36 3/8" x 46 7/8")	1140 x 1420mm (44 7/8" x 55 7/8")
Glass thickness	4mm (5/32")	4mm (5/32")	4mm (5/32")	6mm (1/4")
Perspex thickness	3mm (1/8")	5mm (3/16")	5mm (3/16")	6mm (1/4")
Colour corrected tubes	2 x 610mm (24")	2 x 915mm (36")	3 x 1220mm (48")	4 x 1220mm (48")
3 pin plug (3 amp)	std	std	std	std
Rigid steel frame	std	std	std	std
Stand (with storage racking and tool tray)	opt	opt	std	std
Operating heights with stand	840/890/940mm (33"/35"/37")	840/890/940mm (33"/35"/37")	840/890/940mm (33"/35"/37")	840/890/940mm (33"/35"/37")
Operating positions	level/30°/45°	level/30°/45°	level/30°/45°	level/30°/45°
Chain & sprocket drive	std	std	std	std
Chromed cursors (bevelled, satin finish)	std	std	std	std
Cursor clamps	std	std	std	std
Scales	mm and in. (1/32 div)	mm and in. (1/32 div)	mm and in. (1/32 div)	mm and in. (1/32 div)
Lay-blocks	2	2	2	2
Adjustable film-grips	2	2	2	2
Weight (with stand)	105 kgs	120 kgs	130 kgs	155 kgs