

Stitching Wire



Description:	Round galvanised stitching wire
Applications:	Wire stitching of printed paper
Steel Composition / 100:	Fe 99.47, C 0.58, Si 0.30, Mn 0.60, P 0.10, S 0.26, Ni 0.10, Cr 0.23, Cu 0.10
Coating :	Hot-dip galvanised Zinc
Coating weight g / m ²	13.5 – 16.0
Tensile Strength:	>1000 Nm
Max elongation:	5%
Compatibility:	Automatic and manual stitching equipment, incl. Müller Martini, Ferag, Heidelberg, Hohner etc
Sizes available:	Full range of wire diameters and spool sizes on page 2

HUNTER PENROSE SUPPLIES

consumables for offset printing
www.hunterpenrose.co.uk

Hunter Penrose Supplies Ltd
32 Southwark Street
London SE1 1TU
Tel. 0207 407 5051
info@hunterpenrose.co.uk

Stitching Wire

Wire dimensions

Gauge	Diameter mm	Metres per kg
20	.90	200
21	.80	253
22	.70	331
23	.60	451
24	.55	536
25	.50	649
26	.46	801


Spool sizes – 2.5kg and 15kg

2.5 kg spool

Width:	50mm
Flange diameter:	140mm
Barrel diameter:	53mm
Bore diameter:	20mm

15 kg spool


Width:	100mm
Flange diameter:	300mm
Barrel diameter:	210mm
Bore diameter:	50mm



Bobbin size – 100kg

100 kg bobbin

Diameter:	355mm
Height:	355mm



HUNTER PENROSE SUPPLIES

consumables for offset printing
www.hunterpenrose.co.uk

Hunter Penrose Supplies Ltd
32 Southwark Street
London SE1 1TU
Tel. 0207 407 5051
info@hunterpenrose.co.uk